

Scansione salva-spazio. Versatilità senza limiti.

KX-S1037

Workgroup-volume Scanner / 30ppm



KEY FEATURES

- ADF Scanning (A4)
- Double Feed Skip (DFS) Function
- Push Scan
- Card Scanning
- Up to 30ppm speed

Lo scanner compatto KX-S1037 si distingue per le prestazioni straordinarie e il design salva-spazio, a cui unisce una versatilità di scansione ai vertici della sua classe.

- Il KV-S1037 raggiunge velocità di scansione fino a 30 ppm/60 ipm, a una risoluzione di 300 dpi, a colori
- Grazie alla struttura compatta, questo scanner si adatta perfettamente agli spazi angusti nelle reception o sulle scrivanie da ufficio, nonché nelle aree di assistenza clienti
- Unico nella sua categoria, il KV-S1037 supporta la scansione di passaporti
- Inoltre può gestire documenti di peso variabile da 20 a 431 g/m²
- Produttività giornaliera 3.000 fogli



SPECIFICATIONS

Scanning Face	Duplex
Scanning Method	Color CIS Background: Black
Scanning Resolution	100 - 600 dpi (1 dpi step) and 1200dpi (software) Optical: 300 dpi / 600 dpi
Scanning Speed	Simplex: Up to 30 ppm, Duplex: Up to 60 ipm (Binary / Color, A4 or Letter, 200 / 300 dpi)
Automatic Detection	Intelligent double feed detection used ultrasonic sensor
Image Output	Binary 1-bit, Grayscale 8-bit, Color 24-bit, MultiStream (Color & Binary or Gray & Binary)
Internal Video Processing	1,024 levels (30 bit)
Tonal Gradation	Binary, Grayscale, Color, MultiStream: Binary & Grayscale, Binary & Color
Image Compression	MH, MMR, JPEG, JPEG2000
Binary Mode Halftone	Dither, Error Diffusion
Image Control	Auto preview, Auto rescan, Automatic Brightness Adjustment, Multi Colour Drop Out, Dynamic Threshold, White Level From Paper, Image Emphasis, Gamma, Automatic Separation, Noise Reduction
Other Functions	Length Control, Patchcode Detection (Type 2, 3, T), Control Sheet detection, Long Paper, Double Feed Skip
Documents Paper Size/Thickness/Weight (When 1 page)	Size: 48 mm x 54 mm (1.9 in. x 2.1 in.) - 216 mm x No limited (8.54 in. x No limited) *1 Thickness: 0.04 mm - 0.5 mm (1.6 mils - 19.7 mils) Weight: 20 g/m2 - 413 g/m2 (5.4 lbs. - 91 lbs.) *2 Note: 1 mil = 0.001 in.
Thickness	Paper 0.04 - 0.5 mm (1.6 - 19.7 mils) ISO Card 0.76 mm (29.9 mils) except for emboss 1.24 mm (48.8 mils) include emboss Passport*3 3.0 mm (118.1 mils) include carrier sheet Note: 1 mil = 0.001 in.
Feed Tray Capacity	Up to 50 sheets: A6 to A4 or Letter size 80 g/m2 (21 lbs.,) new paper *4
Supported Operating System	Windows Vista SP2 (32 / 64-bit), Windows 7 (32 / 64-bit), Windows 8 (32 / 64-bit), Windows 8.1 (32 / 64-bit), Windows 10 (32 / 64-bit), WindowsServer2003 SP2 (32 / 64-bit), WindowsServer2003 R2 SP2 (32 / 64-bit), WindowsServer2008 SP2 (32 / 64-bit), WindowsServer2008 R2 SP1
Interface	USB 3.1 interface: Supported Super Speed for Gen1 (Not supported Gen2) Note: If the scanner is connected to a USB hub, it is not guaranteed to work.
External Dimensions (W x D x H)	303 mm x 177 mm x 137 mm (12.0 in. x 7.0 in. x 5.4 in.) (When the exit tray and feed tray are closed.)
Weight	2.7 kg (5.9 lbs.)
Power Requirement	External power supply (AC adaptor) AC 100 V - 240 V, 50 / 60 Hz
Power Consumption Maximum (Scanning)	25 W or less
Power Consumption Minimum (Ready)	6 W or less
Power Consumption (Sleep)	1.6 W or less
Power Consumption (Power Off)	0.3 W or less
Operating Environment	Temperature: 5 to 35 °C (41 to 95 °F) / Humidity: 20 to 80 % RH
Storage Environment	Temperature: -10 to 50 °C (14 to 122 °F) / Humidity: 8 to 75 % RH
Accessories	CD-ROM (Device Driver, ISIS driver software, TWAIN driver software, User Utility,

	Scan Button Setting Tool, Image Capture Plus, Operation manual, Control sheet), Quick Installation Guide, Power cord, AC adaptor, USB cable (1.5m/USB3.1), Mixed
Options Flatbed Scanner	KV-SS081
Consumables Roller Exchange Kit	KV-SS058

URL: <https://business.panasonic.it/soluzioni-per-la-comunicazione/scanner-a4/KX-S1037>

CONTACT

Web: <https://business.panasonic.it/soluzioni-per-la-comunicazione/contact-us>